BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

PITON MULTI PURPOSE LUBRICANT

Creation date 30th March 2023

Revision date Version 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier PITON MULTI PURPOSE LUBRICANT

Substance / mixture mixture

UFI F020-K0MU-F00P-1WR4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

Universal oil for service of various surfaces and mechanisms - cleans, lubricates and provides reliable protection against corrosion. For metal, plastic and rubber.

Main intended use

PC-TEC-11 Lubricants, greases, release agents

Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Importer

Name or trade name BIODUR Sp. z o. o.

Address ul. Modlińska 6a, lok. 224 , Warszawa, 03-216

Poland

Identification number (CRN)6762484086VAT Reg NoPL6762484086Phone+48123766552E-mailinfo@biodur.plWeb addresswww.biodur.pl

Manufacturer

Name or trade name "NEWTON-PROMSERVICE" LLC

Address App. 110 Chichibabina., 9, app. 110, , Charkiw

Ukraine

Phone 0800-31-34-85

E-mail e-marketing@newton.ua

Web address newton.ua

Competent person responsible for the safety data sheet

Name BIODUR Sp. z o. o. E-mail info@biodur.pl

1.4. Emergency telephone number

European emergency number: 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Aerosol 1, H229, H222 Skin Irrit. 2, H315

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Pressurised container: May burst if heated. Extremely flammable aerosol.

Most serious adverse effects on human health and the environment

Causes skin irritation.

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

PITON MULTI PURPOSE LUBRICANT

Creation date 30th March 2023

Revision date Version 1.0

Label elements

Hazard pictogram





Signal word

Danger

Hazardous substances

Kerosine (petroleum) **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C. Dispose of contents/container to by handing over to the person authorized to P501

dispose of waste or by returning to the supplier. 0,87 г/цм³ при 15 °C

Density cat. A (h) SB: 750 g/l VOC limit value

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. **Mixtures**

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

in the working charlothical				
Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 649-404-00-4 CAS: 8008-20-6 EC: 232-366-4	Kerosine (petroleum)	<51	Asp. Tox. 1, H304	
Index: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9	propane	≤35,0	Flam. Gas 1, H220 Press. Gas (liquefied gas), H280	2
Index: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7	butane	≤15,0	Flam. Gas 1, H220 Press. Gas (liquefied gas), H280	1, 2

Notes

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

PITON MULTI PURPOSE LUBRICANT

Creation date 30th March 2023

Revision date Version 1.0

Note U (Table 3): When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible.

If in eves

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

Unlikely.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Not expected.

If on skin

Causes skin irritation.

If in eyes

When intruding eyes, it can evoke irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

PITON MULTI PURPOSE LUBRICANT

Creation date 30th March 2023

Revision date Version 1.0

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Pressurised container: May burst if heated. Extremely flammable aerosol. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale aerosols. Prevent contact with skin and eyes. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Wash hands and exposed parts of the body thoroughly after handling. Do not spray on an open flame or other ignition source. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Protect from sunlight. Do not expose to temperatures exceeding $50\,^{\circ}\text{C}$.

Content	Packaging type	Material of package
400 ml	aerosol can	FE
150 ml	aerosol can	FE

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

8.2. Exposure controls

Take off contaminated clothing and wash before reuse. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

PITON MULTI PURPOSE LUBRICANT

Creation date 30th March 2023

Revision date Version 1.0

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid
Colour od jasnego brązu do ciemnego brązu

Odour characteristic
Melting point/freezing point data not available

Boiling point or initial boiling point and boiling range
Flammability
Lower and upper explosion limit
Flash point
Auto-ignition temperature
Decomposition temperature
DH

Kinematic viscosity

data not available
data not available
data not available
o (undiluted)
data not available
data not available

Kinematic viscosity data not available
Solubility in water data not available
Partition coefficient n-octanol/water (log value) data not available
Vapour pressure data not available

Density and/or relative density

Density 0,87 g/cm³ at 15 °C Relative vapour density data not available Particle characteristics data not available

9.2. Other information

VOC limit value cat. A (h) SB: 750 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. Pressurised container: May burst if heated.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Based on available data the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

PITON MULTI PURPOSE LUBRICANT

Creation date 30th March 2023

Revision date Version 1.0

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

Based on available data the classification criteria are not met.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

Based on available data the classification criteria are not met.

11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

12.2. Persistence and degradability

not available

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not relevant



according to Commission Regulation (EU) 2020/878 as amended

PITON MULTI PURPOSE LUBRICANT

Creation date 30th March 2023

Revision date Version 1.0

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

not available

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.

UN number

Classification code 5F Safety signs 2.



1950

Road transport - ADR

Special provisions 190, 327, 344, 625

Limited quantities 1 L Excepted quantities E0

Packaging

Packing instructions P207, LP200 Special packing provisions PP87, RR6, L2

Mixed packing provisions MP9
Transport category 2
Tunnel restriction code (D)

Special provision for

packages V14 loading, unloading and handling CV9, CV12

operation S2

Railway transport - RID

Special provisions 190, 327, 344, 625

Excepted quantities E

Packaging

Packing instructions P207, LP200 Special packing provisions PP87, RR6, L2

Mixed packing provisions MP9
Transport category 0

Special provision for

packages W 14

loading, unloading and handling CW 9, CW 12

Air transport - ICAO/IATA

Packaging instructions for limited amount Y203
Packaging instructions passenger 203
Cargo packaging instructions 203

Marine transport - IMDG

EmS (emergency plan) F-D, S-U MFAG 620



according to Commission Regulation (EU) 2020/878 as amended

PITON MULTI PURPOSE LUBRICANT

Creation date 30th March 2023

Revision date Version 1.0

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

not available

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H220 Extremely flammable gas. H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

Guidelines for safe handling used in the safety data sheet

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C.
P501 Dispose of contents/container to by handing over to the person authorized to

dispose of waste or by returning to the supplier.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR European agreement concerning the international carriage of dangerous goods by

road

BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of

substance and mixtures

EC Identification code for each substance listed in EINECS

EINECS European Inventory of Existing Commercial Chemical Substances

EmS Emergency plan EU European Union

EuPCS European Product Categorisation System IATA International Air Transport Association

IBC International Code For The Construction And Equipment of Ships Carrying

Dangerous Chemicals

ICAOInternational Civil Aviation OrganizationIMDGInternational Maritime Dangerous GoodsIMOInternational Maritime Organization

INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization
IUPAC International Union of Pure and Applied Chemistry

log Kow Octanol-water partition coefficient
OEL Occupational Exposure Limits

BIODUR®

according to Commission Regulation (EU) 2020/878 as amended

PITON MULTI PURPOSE LUBRICANT

Creation date 30th March 2023

Revision date Version 1.0

PBT Persistent, Bioaccumulative and Toxic

ppm Parts per million

Press. Gas (Comp.)

Press. Gas (Diss.)

Gas under pressure: compressed gas

Gas under pressure: dissolved gas

Press. Gas (Liq.)

Gas under pressure: liquefied gas

Press. Gas (Ref. Liq.) Gas under pressure: refrigerated liquefied gas

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

UN Four-figure identification number of the substance or article taken from the UN

Model Regulations

UVCB Substances of unknown or variable composition, complex reaction products or

biological materials

VOC Volatile organic compounds

vPvB Very Persistent and very Bioaccumulative

Aerosol Aerosol

Asp. Tox. Aspiration hazard
Flam. Gas Flammable gas
Press. Gas Gases under pressure

Skin Irrit. Skin irritation

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.